

**SR30**

Class A Pyranometer with RS-485 Modbus Communications with Integrated Heating and Ventilation



Overview

The SR30, an ISO 9060:2018 spectrally flat Class A (secondary standard) pyranometer manufactured by Hukseflux, features Recirculating Ventilation and Heating (RVH™) technology. As a standalone unit, the SR30 is fully compliant with IEC 61724-1

standards, whereas other pyranometers would require external ventilation/heating units to be compliant. The SR30 is an ideal instrument for solar resource and PV performance monitoring.

Benefits and Features

- ▶ Heated for high data availability, featuring RVH™ technology
- ▶ Compliant with IEC 61724-1:2021 Class A

- ▶ Remote sensor diagnostics

Specifications

Sensor	High-quality blackened thermopile protected by two glass domes with integrated heater and ventilation
--------	---

Measurement Description	Monitors solar radiation for the full solar spectrum range
-------------------------	--

Hemispherical Solar Radiation

Heater	RVH™ (Recirculating Ventilation and Heating)
ISO Classification	Spectrally flat Class A (secondary standard) ISO 9060:2018
IEC 61724-1:2021 Compliance	Class A

Calibration Uncertainty	< 1.2% (k = 2)
Heating	Included
Ventilation	Included
Technology Employed	Recirculating Ventilation and Heating (RVH™)
Standard Operating Mode	Heated and ventilated
Power Consumption @ 12 Vdc	< 2.3 W
Zero Offset A	< 2 W/m ²
Calibration Traceability	To WRR
Calibration Registers	Accessible to users
Spectral Range	285 to 3000 x 10 ⁻⁹ m



Sensitivity	Digital output
Operating Temperature Range	-40 to +80°C (rated)
Temperature Response	< ±0.4% (-30 to +50°C)
Temperature Response Test Report included of Individual Instrument	
Directional Response Test of Individual Instrument	Report included
Rated Operating Voltage Range	8 to 30 Vdc

Sensor Tilt Angle

Tilt Measurement Uncertainty	±1° (0 to 90°)
Tilt Sensor Test of Individual Report included Instrument	

Operation in Low-Power Mode	
Operating Condition	Heater and ventilator [OFF]
Zero Offset A	5 W/m ² (unventilated)

Power Consumption @ 12 Vdc	< 0.1 W
----------------------------	---------

Digital Output	
Output	» Modbus RS-485
	» Ventilator speed in RPM
	» Internal humidity in %
	» Tilt angle in °
	» Instrument body temperature in °C
	» Irradiance in W/m ²
Communication Protocol	Modbus over two-wire RS-485
Transmission Mode	RTU